

## Comparison List

Product Details	Testing Description	Bone Dry Pro Sealer	VaporSeal 309	Spray Lock SCP 327/578	Sinak VC-5	Traxx Liquishield-100	Concure MVE Vapor Barrier +
<b>Film Forming</b>		No	Yes	No	Yes	Yes	No
<b>Bond Breaker</b>		No	no data	No	No	No	No
<b>Moisture Testing Required</b>		No	Yes	No	No	No	No
<b>Maximum Concrete Water to Cement Ratio</b>		No Requirement	No Requirement	No Requirement	No Requirement	No Requirement	0.5
<b>Demo and Reinstallation of Finished Flooring Allowed</b>		Yes	no data	Yes	Yes	No Data	No Data
<b>Moisture Limitations</b>		25 lbs/1000sqft, 100% RH	no data	20 lbs/1000sqft, 100% RH	100% RH	25 lbs/1000sqft, 100% RH	No Data
<b>ASTM E 96 Testing</b>	Water Vapor Transmission	0.3 grams/m or 1.2 perms	no data	70% reduction (no data)	.08 grams/m	No Data	1.41 perms
<b>ASTM F 1869 Testing</b>	Moisture Vapor Emission Rate using Calcium Chloride	2.81 lbs/1000 sqft/24 hrs	<5 lbs/1000 sqft/24hrs	no data	<5 lbs/1000 sqft/24hrs	No Data	2.3 lbs/1000 sqft/24 hrs
<b>ASTM D 7234</b>	Adhesion Pull Testing	650 psi	no data	no data	No Data	"High" No Data	490 psi
<b>Warranty Duration</b>		25 Years	10-15 years	25 Years	20 Years	10 Years	"Up To" Lifetime Warranty (Bond Test Required)
<b>Warranty Inclusions</b>		Finished Flooring System, Adhesive, Patching and leveling compounds	Finished Flooring System Only	Finished Flooring System Only	Finished Flooring System and Adhesives	Finished Flooring System, Adhesive, Patching and leveling compounds	Finished Flooring System Only