

BONEdry

Provides a superior seal to prevent salts and other deicing material from penetration and deteriorating the concrete. Densifies and protects the concrete from freeze/thaw related damage. Prevents cracking and spalling and significantly increases abrasion resistance. Increases the service life of the slab.

SEALING: Bone Dry Driveway Sealer seals concrete into a mass that is essentially solid, rather than porous. Its penetrating quality provides deep sealing and an effective seal for the life of the concrete.

FREEZE/THAW PROTECTION:

Bone Dry Driveway sealer prevents moisture from absorbing deep into the concrete causing freeze thaw damage to the surface of the slab.

DENSIFYING: Bone Dry Driveway Sealer makes concrete substantially harder initially and independent testing shows it to be 23% stronger.

WATERPROOFING: Bone Dry Driveway Sealer becomes an integral permanent part of the concrete by waterproofing and strengthening the structure of the concrete.

Abrasion Resistance: Bone Dry Driveway Sealer strengthens the concrete surface reducing the slabs susceptibility to surface wear and tear due to traffic.

Bone Dry Products, Inc.
9009 58th Place
Kenosha, WI 53144
262.694.9748
info@bonedryproducts.com

| | |
|--|---|
| HEALTH | 1 |
| FLAMMABILITY | 0 |
| REACTIVITY | 0 |
| CONSULT SDS FOR ADDITIONAL INFORMATION | |

BONEdry

PRODUCTS, Inc.

DRIVEWAY SEALER

PERMANENTLY WATERPROOFS CONCRETE • NON-TOXIC
COST EFFECTIVE • EASY TO APPLY • LOW ODOR

DIRECTIONS

- 1 Wash the slab free of any dirt and debris so as to apply the Bone Dry Driveway Sealer to a clean surface.
- 2 Use Bone Dry at full strength. *DO NOT DILUTE.*
- 3 Saturate the surface with the Bone Dry sealer. Application can be made with an battery powered sprayer or hand pumped garden type sprayer.
- 4 After completing a section, let the product absorb into the concrete for no more than 10 minutes and apply a second coat. When applying a second coat only apply to the areas where the sealer has penetrated, and the texture of the concrete has become visible.
- 5 Allow the sealer to become dry to the touch prior to walking or driving on the concrete.

Spread

200-250 square feet per gallon

Storage

Product must be stored in conditions above freezing and below 90 degrees Fahrenheit. The shelf life of product is 2 years.

APPLICATION VIDEO:

www.bonedryproducts.com/video



**KEEP OUT OF REACH OF CHILDREN
CONSULT SDS SHEET BEFORE USING**

WARNING: Do not apply to glass, metal or any other finish surface. If so wipe off with wet rag immediately.



5 Gal. (18.92 L)

www.BoneDryProducts.com