



For Remodels Utilizing Existing Concrete Slabs:
Approved Cementitious Top Coatings

Warranty: Bone Dry Products warrants the bond of these products to the concrete substrate. Remodeled Concrete substrates must be profiled to a CSP 2 (diamond ground or shot blasted) prior to receiving a cementitious top coating. Cementitious top coatings for remodel projects must be applied a minimum thickness of 1/8".

Ardex

SD-P LT
B 24
B 40
K 34
K 525
K 530
K 40 Rapid
Feather Finish XF
Feather Finish
TL 2000
TL 1400
TL 1000
K 523
MRF
Liquid Backboard
AM 100
SKM
Forti-Finish
K 15
K 301
SD-M
SD-P Rapid
SD-P
SD-T
V 1200
PC-T
K 10
K 13
K 22 F
K 520
V 1000
CP
CD Fine
CD
GPS
TRM
ERM

Laticrete

NXT® Level Plus Lite
NXT® Level Plus
NXT® Level
SC500-PLUS
SC500
SUPERCAP® SC500-LW
NXT® Level DL
NXT® Level SP
Skim Lite
NXT® Patch
3701 Lite Mortar
3701 Lite Mortar R
3701 Fortified Mortar Bed
209 Floor Mud

Sika

SikaLevel -025 Patch
SikaLevel®
SikaLevel SkimCoat
SikaQuick®-1000
Sika® Level-125
Sika® Level-225
Sika® Level-325

Uzin

NC 144 LW
NC 147 CG
NC 150
NC 150 F
NC 157
NC 170
NC 172 TURBO

Mapei

Planipatch
Planiprep SC
Novoplan DPL
Novoplan Easy Plus
Self-Leveler Plus
Novoplan 2 plus
Novoplan NFL
Ultraplan-Plus
Ultraplan Easy
Ultraplan Extreme 2
Ultraplan Lite
Ultraplan M20 Plus

Schonox

SL
RF
HS Sturdy
PL
SEZ Plus
SGH
AP Rapid
AP Rapid Plus
ZM
ZM Rapid
XM
US

Quickrete

QUIKRETE® Q•Max Pro Concrete Mix
QUIKRETE® EA Concrete Repair Mix
QUIKRETE® Fast-Setting Concrete Mix
Underlayment - Fast-Setting
FastSet® Concrete Mix
Concrete mix
Quickrete 5000
Crack Resistant
FastSet Non-Shrink Grout
FastSet DOT Mix

Note: Additional Products may be approved upon request.

Contact: Bone Dry Products

info@bonedryproducts.com

Ph: 262-694-9748