

SAFETY DATA SHEET

Issue Date 15-Oct-2023 Revision Date 15-Oct-2023 Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name Bone Dry Degreaser

Other means of identification

Product Code 16-1 Synonyms None

Details of the supplier of the safety data sheet

Company Name Bone Dry Products

9009 58th PI Kenosha, WI 53144

Emergency telephone number

Emergency Telephone

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 5
Acute toxicity - Dermal	Category 5
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1

Label elements

Emergency Overview

Danger

Hazard statements

May be harmful if swallowed Causes severe skin burns and eye damage



Appearance Clear Blue Physical state Liquid Odor Mild Sweet Solvent

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Specific Treatment (See Section 4 on the SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Drink plenty of water

Immediately call a POISON CENTER or doctor/physician

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations

Hazards not otherwise classified (HNOC)

Other Information

Unknown Acute Toxicity 0.03799% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
2-butoxyethanol	111-76-2	1-5	*
Potassium Hydroxide	1310-58-3	>1	*
Monoethanolamine	141-43-5	>1	*
Sodium Metasilicate	6834-92-0	>1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice Immediate medical attention is required.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. For minor skin contact, avoid spreading material on unaffected skin. For

severe burns, immediate medical attention is required.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area.

Inhalation Remove to fresh air. Get medical attention for any breathing difficulty.

Ingestion Rinse mouth. Do NOT induce vomiting. Drink plenty of water. Call a physician or poison

control center immediately.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Any additional important symptoms and effects are described in Section 11: Toxicology

Information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosiv

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. In the event of fire and/or explosion do not breathe fumes.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak. Use personal protective equipment as required.

Environmental precautions

Environmental precautionsDo not allow into any storm sewer drains, lakes, streams, ponds, estuaries, oceans or other

surface water bodies. Should not be released into the environment. Dispose of according to

all local city, state and federal rules and regulations.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning upDike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take

up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Prevent product from entering drains. Dam up. After cleaning, flush away traces

with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handlingUse personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed

systems.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep out of the reach of children. Keep container tightly closed in a dry and well-ventilated

place. Keep in properly labeled containers.

Incompatible materials

Strong acids. Aluminum. Incompatible with strong acids and bases. Incompatible with

oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Potassium Hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Monoethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m³	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m³ STEL: 6 ppm STEL: 15 mg/m³
Diethanolamine 111-42-2	TWA: 1 mg/m³ inhalable fraction and vapor S*	(vacated) TWA: 3 ppm (vacated) TWA: 15 mg/m³	TWA: 3 ppm TWA: 15 mg/m³
Sodium Hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m³ (vacated) Ceiling: 2 mg/m³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacate

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers, Eyewash stations & Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Wear a face shield if splashing hazard exists.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene When using do not eat, drink or smoke. Keep away from food, drink and animal feeding

stuffs. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Take off all contaminated clothing and wash it before reuse. Wear suitable

gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state
Appearance
Color
Liquid
Clear Blue
Blue

Odor Mild Sweet Solvent
Odor threshold No Information available

Property Values Remarks • Method

pH 13.0 - 14.0 Specific Gravity 1.065

Viscosity < 25 cP @ 25°C

Melting point/freezing point No Information available

Flash point > 140 °F

Boiling point / boiling range 100 °C / 212 ° F Degrees

Evaporation rate No Information available Flammability (solid, gas) No data available

Flammability Limits in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No Information available
No Information available
No Information available

Water solubility Complete
Partition coefficient No Information available

Autoignition temperature

No Information available

No Information available

No Information available

Other Information

Density Lbs/Gal 8.87 VOC Content (%) 10

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Exposure to air or moisture over prolonged periods.

Incompatible materials

Strong acids. Aluminum. Incompatible with strong acids and bases. Incompatible with oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product InformationThe primary effects and toxicity of this material are due to it corrosive nature.

Inhalation Avoid breathing vapors or mists. Breathing of vapor can cause respiratory irritation and

inflammation. Breathing of mist or liquid can cause burns to the respiratory tract.

Eye contact Avoid contact with eyes. Corrosive. Causes severe eye damage.

Skin Contact May be harmful in contact with skin. Avoid contact with skin. Corrosive. Contact with skin

may cause severe irritation and burns. Maybe harmful if absorbed through skin.

Ingestion May be harmful if swallowed. Ingestion causes acute irritation and burns to the mucous

membranes of the mouth, trachea, esophagus and stomach. Ingestion may result in the absorption of potentially harmful amounts leading to possible liver and kidney damage.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Potassium Hydroxide 1310-58-3	= 284 mg/kg (Rat)	-	-
Monoethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1000 mg/kg (Rabbit)	-
Sodium Metasilicate 6834-92-0	= 1153 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms No Information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Corrosivity Causes burns. Extremely corrosive and destructive to tissue. Risk of serious damage to

eves.

Sensitization No Information available.

Germ cell mutagenicity No Information available.

CarcinogenicityThe table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-butoxyethanol	A3	Group 3	-	-
111-76-2				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 -Not classifiable as a human carcinogen

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No Information available.
No Information available.

Chronic toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Possible risk of irreversible effects. May cause adverse effects on the bone marrow and

blood-forming system. May cause adverse liver effects.

Target organ effects Blood, Central nervous system, EYES, hematopoietic system, Kidney, Liver, Respiratory

system, Skin.

Aspiration hazard No Information available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.03799% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 3,707.00 ATEmix (dermal) 4,950.50 ATEmix (inhalation-dust/mist) 15.00

12. ECOLOGICAL INFORMATION

Ecotoxicity

0.03799% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-butoxyethanol	-	1490: 96 h Lepomis macrochirus	1000: 48 h Daphnia magna mg/L
111-76-2		mg/L LC50 static	EC50
		2950: 96 h Lepomis macrochirus	
		mg/L LC50	
Monoethanolamine	15: 72 h Desmodesmus subspicatus	114 - 196: 96 h Oncorhynchus	65: 48 h Daphnia magna mg/L
141-43-5	mg/L EC50	mykiss mg/L LC50 static	EC50
		300 - 1000: 96 h Lepomis	
		macrochirus mg/L LC50 static	
		227: 96 h Pimephales promelas	
		mg/L LC50 flow-through	

Revision Date 15-Oct-2023

Bone Dry Degreaser

		3684: 96 h Brachydanio rerio mg/L	
		LC50 static	
		200: 96 h Oncorhynchus mykiss	
		mg/L LC50 flow-through	
Sodium Metasilicate	-	210: 96 h Brachydanio rerio mg/L	-
6834-92-0		LC50	
		210: 96 h Brachydanio rerio mg/L	
		LC50 semi-static	
Tetrasodium EDTA	1.01: 72 h Desmodesmus	41: 96 h Lepomis macrochirus mg/L	-
64-02-8	subspicatus mg/L EC50	LC50 static	
	January Mg/ = 2000	59.8: 96 h Pimephales promelas	
		mg/L LC50 static	
Sodium Sulfate	_	13500 - 14500: 96 h Pimephales	2564: 48 h Daphnia magna mg/L
7757-82-6		promelas mg/L LC50	EC50
1.0.02		3040 - 4380: 96 h Lepomis	
		macrochirus mg/L LC50 static	
		13500: 96 h Lepomis macrochirus	
		mg/L LC50	
		6800: 96 h Pimephales promelas	
		mg/L LC50 static	
Diethanolamine	2.1 - 2.3: 96 h Pseudokirchneriella	1200 - 1580: 96 h Pimephales	55: 48 h Daphnia magna mg/L
111-42-2	subcapitata mg/L EC50	promelas mg/L LC50 static	EC50
	7.8: 72 h Desmodesmus	4460 - 4980: 96 h Pimephales	
	subspicatus mg/L EC50	promelas mg/L LC50 flow-through	
	9	600 - 1000: 96 h Lepomis	
		macrochirus mg/L LC50 static	
Trisodium nitrilotriacetate	-	175 - 225: 96 h Lepomis	560 - 1000: 48 h Daphnia magna
5064-31-3		macrochirus mg/L LC50 static	mg/L LC50
		560 - 1000: 96 h Oryzias latipes	ű
		mg/L LC50	
		560 - 1000: 96 h Oryzias latipes	
		mg/L LC50 semi-static	
		560 - 1000: 96 h Poecilia reticulata	
		mg/L LC50	
		560 - 1000: 96 h Poecilia reticulata	
		mg/L LC50 semi-static	
		72 - 133: 96 h Oncorhynchus	
		mykiss mg/L LC50 static	
		93 - 170: 96 h Pimephales promelas	
		mg/L LC50 flow-through	
		114: 96 h Pimephales promelas	
		mg/L LC50	
		252: 96 h Lepomis macrochirus	
		mg/L LC50	
		470: 96 h Pimephales promelas	
		mg/L LC50 static	
Sodium Hydroxide	-	45.4: 96 h Oncorhynchus mykiss	-
1310-73-2		mg/L LC50 static	

Persistence and degradability

No Information available.

Bioaccumulation

Bioaccumulative potential.

Chemical Name	Partition coefficient
2-butoxyethanol	0.81
111-76-2	
Potassium Hydroxide	0.65
1310-58-3	0.83
Monoethanolamine	-1.91
141-43-5	

Other adverse effects

No Information available

13. DISPOSAL CONSIDERATIONS

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Potassium Hydroxide	Toxic
1310-58-3	Corrosive

14. TRANSPORT INFORMATION

Per CFR 173.154 (b)(2), for corrosive materials in Packaging Group III, this product can ship as Limited Quantity if packaged not over 5.0 L (1.3 gallon) net capacity each for liquids or not over 5.0 kg (11 lbs) net capacity each for solids, packed in a strong outer packaging. Must not exceed 30 kg (66 pounds) gross weight.

DOT

UN/ID No. UN1760

Proper shipping name Corrosive liquids, n.o.s.

Hazard Class 8
Packing Group III

Special Provisions IB3, T7, TP1, TP28

Description UN1760, Corrosive liquids, n.o.s (contains Potassium Hydroxide and Ethanolamine), 8, III

Emergency Response Guide 15

Number

TDG

UN/ID No. UN1760

Proper shipping name Corrosive liquids, n.o.s.

Hazard Class 8
Packing Group III

Description UN1760, Corrosive liquids, n.o.s. (contains Potassium Hydroxide and Ethanolamine), 8. III

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-butoxyethanol - 111-76-2	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21

and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium Hydroxide 1310-58-3	1000 lb	-	-	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Potassium Hydroxide	1000 lb	=	RQ 1000 lb final RQ
1310-58-3			RQ 454 kg final RQ

US State Regulations

California Proposition 65

WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the state of California to cause cancer. For More Information go to www.P65Warnings.ca.gov.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-butoxyethanol 111-76-2	Х	X	X
Potassium Hydroxide 1310-58-3	Х	X	X
Monoethanolamine 141-43-5	Х	X	X
Sodium Sulfate 7757-82-6	-	X	X
Diethanolamine 111-42-2	Х	X	X
Trisodium nitrilotriacetate 5064-31-3	-	X	-
Sodium Hydroxide 1310-73-2	Х	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not Applicable

<u>NFPA</u>	Health hazards 3	Flammability 0	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 3	Flammability 0	Physical hazards 0	Personal protection C

16. OTHER INFORMATION

Issue Date27-Jan-2021Revision Date27-Jan-2021Revision Note27-Jan-2021

No Information available

<u>Disclaimer</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.