



## Specifications

### Bone Dry Pro Gyp-Cap



## Description

Bone Dry Pro Gyp-Cap is a single-component, ready-to-use membrane-forming surface coating engineered for superior moisture mitigation, capable of handling up to 100% relative humidity on gypsum-based substrates. It effectively protects against dusting, applies effortlessly by spray or roller, and is fully compatible with gypcrete over plywood subfloors. Additionally, this solvent-free product requires no profiling or primer before applying underlayment or finished flooring adhesives, is resealable for convenience, and allows foot traffic in as little as 60 minutes.

## Preparation

- Allow the gypsum to dry for 5-7 days prior to application.
- Ensure existing gypcrete surfaces are completely free of any surface buildup, water-based adhesives, and contaminants
- Verify the substrate is smooth, porous, sound, and clean to ensure optimal adhesion.
- Maintain a dew point at least 5 degrees F away from the substrate temperature to avoid surface condensation.

## Application Equipment

Apply Bone Dry Pro Gyp-Cap utilizing a pump or battery-powered sprayer equipped with a wide fan tip. Alternatively, a brush or heavy-nap roller may be employed if preferred.

## Application

Gypsum based substrates must be broom-swept or vacuumed to eliminate any residual construction debris and dust from the slab. Particles not removed prior to application will become entrapped beneath the Bone Dry Pro Gyp-Cap. Apply a single, uniform coat to the slab, and allow the sealer to dry for a minimum 60 minutes before proceeding with the installation of underlayment or the finished flooring system.

## Spread

200-300 sqft per gallon

## **Patch and Leveling Compounds**

Patch and leveling compounds must be compatible with non-porous substrates when applying directly to the Bone Dry Pro Gyp-Cap.

## **Adhesives**

### **Approved Adhesives**

Bone Dry Products approves the use of the flooring manufacturers recommended adhesives for non-porous substrates when adhering directly to the Bone Dry Pro Gyp-Cap.

### **Adhesive Application**

Adhesives applied directly to the sealed concrete surface must be applied as per specifications for a non-porous substrate.

## **Contact**

Bone Dry Products  
9009 58th Pl  
Kenosha, WI 53144  
262-694-9748  
Email: [info@bonedryproducts.com](mailto:info@bonedryproducts.com)

## **Warranty Information**

Please contact Bone Dry Products for details on our project specific 25 year commercial warranty which includes material and labor to replace the prep material, adhesive, and finished flooring if there is a concrete moisture related failure.