



## Specifications

### Bone Dry Pro Gyp-Cap



## Description

Bone Dry Pro Gyp-Cap is a single-component, ready-to-use membrane-forming coating engineered for new construction. Formulated specifically for gypcrete over plywood substrates, it provides superior moisture mitigation capable of handling up to 100% relative humidity. This solvent-free product protects against dusting, requires no profiling or primer prior to installing underlayment or finished flooring adhesives, is resealable, and allows foot traffic in as little as 60 minutes.

## Preparation

- Allow the gypcrete to cure for a minimum of 5–7 days prior to application.
- Ensure the gypcrete surface is free of surface buildup, water-based adhesives, and contaminants prior to application.
- Verify the substrate is smooth, porous, sound, and clean to ensure optimal adhesion.
- Maintain a dew point at least 5 degrees F away from the substrate temperature to avoid surface condensation.

## Application Equipment

Apply Bone Dry Pro Gyp-Cap with a pump or battery-powered sprayer fitted with a wide fan tip. A brush or heavy-nap roller may also be used.

## Application

The gypcrete surface must be thoroughly broom-swept or vacuumed to remove all construction debris and dust. Any particles left on the surface will become trapped beneath the Bone Dry Pro Gyp-Cap membrane. Apply a single, uniform coat and allow to dry for a minimum of 60 minutes before installing underlayment or the finished flooring system.

## Spread

200-300 sqft per gallon

## **Patch and Leveling Compounds**

Patch and leveling compounds must be compatible with non-porous substrates when applying directly to the Bone Dry Pro Gyp-Cap.

## **Adhesives**

### **Approved Adhesives**

Bone Dry Products approves the use of the flooring manufacturers recommended adhesives for non-porous substrates when adhering directly to the Bone Dry Pro Gyp-Cap.

### **Adhesive Application**

Adhesives applied directly to the Bone Dry Pro Gyp-Cap-sealed surface must be applied per the flooring manufacturer's specifications for non-porous substrates.

## **Contact**

Bone Dry Products  
9009 58th Pl  
Kenosha, WI 53144  
262-694-9748  
Email: [info@bonedryproducts.com](mailto:info@bonedryproducts.com)

## **Warranty Information**

Please contact Bone Dry Products for details on our project specific 25 year warranty on commercial projects which includes material and labor to replace the prep material, adhesive, and finished flooring if there is a concrete moisture related failure.